

- 1. CURB W/ APRON 11 GA. ALUMINIUM
- 3. COVER LINER 18 GA. ALUMINIUM
- 4. 1" [25MM] FIBERGLASS CURB INSULATION
- 5. 2" [50MM] POLYISOCYANURATE COVER INSULATION
- 6. EPDM GASKET (ALL AROUND COVER)
- 7. PINTLE HINGE STAINLESS STEEL TYPE 316
- 9. SLAM LATCH WITH INSIDE AND OUTSIDE HANDLES W/ PADLOCK HASPS (HANDLES TO BE INSTALLED ON SITE BY CUSTOMER)
- 10. LOCK STRIKE AND PADLOCK HASP
- 11. LIFTING MECHANISM WITH REINFORCED COMPOSITE TUBES AND COMPRESSION SPRINGS
- 12. AUTOMATIC HOLD OPEN ARM W/ RED VINYL GRIP

HARDWARE: CORROSION RESISTANT

(UNLESS OTHERWISE SPECIFIED)

- 1. THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE
- 2. FULL SPECIFICATIONS ARE AVAILABLE ON WEBSITE:

Manufacturers of Doors for Special Services THE BILCO COMPANY New Haven, Connecticut 06505

## SINGLE LEAF ROOF ACCESS HATCH **TYPE S-50VMT**

SIZE WIDTH x LENGTH

3'-0" x 2'-6" 915mm x 760mm

HINGE SIDE WEB SITE: www.bilco.com