

## SPECIFICA TIONS

- CURB, FULLY ENCLOSED W/ INTEGRAL CAP FLASHING (CORNERS FULLY WELDED) 10 GA. GALVANNEAL STEEL
- 2. COVER 14 GA. GALVANNEAL STEEL
- 3. COVER LINER 12 GA. GALVANNEAL STEEL
- 4. 4" CURB INSULATION
- 5. 4" COVER INSULATION
- 6. GASKET (ALL AROUND)
- 7. PIANO HINGE
- 8. BILCLIP® FLASHING SYSTEM
- 9. FIXED CENTER DRAIN
- GAS SPRINGS W/ DAMPER & HOLD OPEN FEATURE (CORROSION RESISTANT)
- 11. TRACTION SPRING
- 12. COVER RESTRAINT CABLE
- 13. COVER LATCH BRACKET
- 14. THERMOLATCH POSITIVE HOLD/RELEASE MECHANISM
- 15. 165° FUSIBLE LINK (EXTRA LINK PROVIDED)
- 16. INTERIOR PULL RELEASE CABLE
- 17. EXTERIOR PULL RELEASE CABLE

## SHOP FINISH

STEEL: RED OXIDE PRIMER

HARDWARE: ZINC PLATED/CHROMATE SEALED

(UNLESS OTHERWISE SPECIFIED)

## NOTES:

- 1. THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE FACTORY FOR MODIFICATION.
- 2. FULL SPECIFICATIONS ARE AVAILABLE ON WEBSITE: WWW.BILCO.COM

<u>CUSTOMER</u> :		
<u>P.O. NO</u> :		
<u>JOB</u> :		
<u>TAG</u> :		
<u>SALES REP</u> :		
<u>APPROVED BY:</u>		
DATE:		

Manufacturers of Doors for Special Services •صعالنكا THE BILCO COMPANY New Haven, Connecticut 06505

## **DOUBLE LEAF SMOKE VENT TYPE ACDSV**

QTY	MODEL	SIZE width x length	24 THE BILC
		X HINGE SIDE	€ 08-02-