



SECTION

SPECIFICATIONS

1. FRAME W/ CAPFLASHING (CORNERS FULL WELDED)
 - SS-20 - 14 GAUGE P.B. GALV. STEEL
 - SS-40 - 14 GAUGE P.B. GALV. STEEL
 - SS-50 - 11 GAUGE ALUMINUM
2. PINTLE HINGE
3. GASKET (ALL AROUND COVER)
4. COVER GAUGE
 - SS-20 - 14 GAUGE P.B. GALV. STEEL
 - SS-40 - 11 GAUGE ALUMINUM
 - SS-50 - 11 GAUGE ALUMINUM
5. COVER LINER
 - SS-20 - 22 GAUGE P.B. GALV. STEEL
 - SS-40 - 18 GAUGE ALUMINUM
 - SS-50 - 18 GAUGE ALUMINUM
6. SPRING LIFTING MECHANISM
7. 1" RIGID FIBERBOARD INSULATION
8. SLAM LATCH
9. INSIDE AND OUTSIDE HANDLES W/ PADLOCK HASPS
10. ARM GUIDE BRACKET
11. 1" THICK FIBERGLASS COVER INSULATION
12. HOLD OPEN ARM W/ RED VINYL GRIP
13. NEOPRENE GASKET
14. LOCK STRIKE & PADLOCK HASP
15. BILCLIP® FLASHING SYSTEM
16. GUIDE ARM
17. HANDRAIL (1 1/4" SCH 40 PIPE, SAME MATERIAL AS COVER)

SHOP FINISH:
 STEEL: RED OXIDE PRIMER
 ALUMINUM: MILL FINISH
 HARDWARE: NON-CORROSIVE MATERIALS
 (UNLESS OTHERWISE SPECIFIED)

THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HINGE SIDE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE FACTORY FOR MODIFICATION.

CUSTOMER:

P.O. N°

JOB:

SALES REP:

Manufacturers of Doors for Special Services
Bilco® THE BILCO COMPANY
 New Haven, Connecticut 06505

SINGLE LEAF ROOF SCUTTLE MODIFIED FOR 68° LAPEYRE STAIR
 TYPE SS SIZE x WIDTH x LENGTH
 METAL

QTY	TYPE	WIDTH x LENGTH
<input type="checkbox"/>	SS-20	STEEL COVER/STEEL FRAME
<input type="checkbox"/>	SS-40	ALUM. COVER/STEEL FRAME
<input type="checkbox"/>	SS-50	ALUM. COVER/ALUM. FRAME

THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATES INFORMATION WHICH IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.